

AMENDMENT TO THE CLAIMS

A complete listing of the claims is as follows:

---

Claim 1. (*Previously Presented*) A ventilated sport shoe including a lower frame portion mounting a bearing member, wherein the ventilated sport shoe comprises:

an upper shoe portion defining an interior adapted to receive a foot; and

a foot bed including a base secured to the upper shoe portion, the foot bed defining an upper surface capable of receiving the foot and the base defining a lower surface capable of mounting the lower frame thereon, the foot bed defining a ventilation channel formed within or below the upper surface of the foot bed and at least partially traversing the foot bed from an inlet aperture defined on an exterior of the lower surface of the base to an outlet aperture defined on the exterior of the lower surface of the base, the apertures providing ambient airflow into and out of the foot bed from the exterior of the base during use, wherein the ventilation channel is in moisture transport communication with the interior of the upper shoe portion, thereby providing ventilation and moisture transfer from the received foot to the channel and out of the outlet aperture.

Claim 2. (*Original*) The ventilated sport shoe of claim 1, wherein the upper shoe portion is configured for ventilation of upper portions of the foot.

Claim 3. (*Original*) The ventilated sport shoe of claim 1, wherein the inlet aperture is defined by the base and is longitudinally spaced from the outlet aperture relative to a longitudinal axis of the base.

Claim 4. (*Original*) The ventilated sport shoe of claim 3, wherein the inlet aperture is defined adjacent a toe portion of the base and the outlet aperture is defined adjacent a heel portion of the base.

Claim 5. (*Original*) The ventilated sport shoe of claim 4, wherein the inlet and outlet apertures and the ventilation channel are configured to provide continuous airflow therebetween for the length of the sport shoe, thereby providing ventilation and moisture transfer for substantially the entire length of the foot.

Claim 6. (*Original*) The ventilated sport shoe of claim 4, further comprising at least one branch ventilation channel extending from a branch inlet aperture, defined on the exterior of the base between the toe portion and the heel portion, rearwardly to join the ventilation channel.

Claim 7. (*Original*) The ventilated sport shoe of claim 6, further comprising a plurality of branch ventilation channels.

Claim 8. (*Original*) The ventilated sport shoe of claim 1, wherein the lower surface of the base defines a projection projecting downwardly from the lower surface, the inlet ventilation aperture being defined within the projection.

Claim 9. (*Original*) The ventilated sport shoe of claim 8, wherein the inlet ventilation aperture is disposed on a forward face of the projection, such that the forward face is oriented towards a toe portion of the base.

Claim 10. (*Original*) The ventilated sport shoe of claim 9, wherein the inlet ventilation aperture is positioned normal to the freestream airflow through the ventilation channel, thereby drawing airflow through the channel.

Claim 11. (*Original*) The ventilated sport shoe of claim 1, wherein the ventilation channel comprises a plurality of channels at least partially traversing the upper surface of the foot bed providing airflow into and out of the foot bed for corresponding portions of the foot bed during use.

Claim 12. (*Original*) The ventilated sport shoe of claim 11, wherein the plurality of ventilation channels are arranged to ventilate at least a majority of the upper surface of the foot bed.

Claim 13. (*Original*) The ventilated sport shoe of claim 11, wherein the plurality of channels are disposed substantially parallel to a longitudinal axis of the foot bed.

Claim 14. (*Original*) The ventilated sport shoe of claim 11, wherein the plurality of channels are arranged over or within substantially the entire width of the upper surface of the foot bed.

Claim 15. (*Original*) The ventilated sport shoe of claim 1, wherein the ventilation channel is configured for at least a portion of its length as a groove formed in the upper surface of the base.

Claim 16. (*Previously Presented*) The ventilated sport shoe of claim 1, wherein the ventilated sport shoe is adapted for use as an in-line skate shoe, further comprising a lower frame secured to the base and a plurality of longitudinally aligned wheels mounted on the lower frame.

Claim 17. (*Original*) The ventilated sport shoe of claim 1, wherein the ventilation channel is defined in the base and the foot bed further comprises a substrate received within the upper shoe portion between an upper surface of the base and a user's foot, the substrate defining a plurality of moisture transport pathways in fluid communication with the ventilation channel.

Claim 18. (*Original*) The ventilated sport shoe of claim 17, wherein the substrate comprises a last board received on the upper surface of the base and joining the upper shoe portion to the base.

Claim 19. (*Original*) The ventilated sport shoe of claim 18, wherein the last board defines a plurality of apertures vertically extending therethrough at least partially aligned and in fluid communication with the ventilation channel.

Claim 20. (*Canceled*)

Claim 21. (*Canceled*)

Claim 22. (*Original*) An in-line skate including a plurality of wheels, comprising:  
an upper shoe portion defining an interior adapted to surround a user's foot;  
a foot bed including a base secured to the upper shoe portion, the foot bed having

an upper surface that supports the user's foot and the base having an exterior surface, wherein the base defines inlet and outlet ventilation apertures on the exterior surface of the base, and the foot bed defines a channel extending from the inlet to the outlet aperture and at least partially along the upper surface of the foot bed to provide ambient airflow into and out of the foot bed from the exterior of the base during use;

moisture transport means for placing the channel in moisture transport communication with the interior of the upper shoe portion, such that motion of the skater during use causes airflow from the inlet aperture through the channel to the outlet aperture to draw moisture from the interior of the skate; and

a frame for mounting the plurality of wheels secured to the exterior of the base.

① Claim 23. (*Previously Presented*) A ventilated sport shoe base having an upper shoe portion adapted to receive a foot and a lower load-bearing surface, wherein the ventilated sport shoe comprises:

a base adapted to receive the upper shoe portion, the base defining an upper surface capable of receiving the foot and a lower surface capable of mounting the load-bearing surface, the base defining a ventilation channel at least partially traversing the upper surface of the base from an inlet aperture to an outlet aperture, the inlet and outlet apertures being defined on an exterior of the base to provide ambient airflow into and out of the base from the exterior of the base during use; and

a substrate received within the upper shoe portion on the upper surface of the base and including a plurality of moisture transport pathways therethrough wherein air{flow} can flow from the aperture, through the ventilation channel, and out the outlet aperture, drawing moisture from the foot through the moisture transport pathways.

Claim 24. (*Previously Presented*) A ventilated sport shoe including a lower frame portion mounting a bearing member, wherein the ventilated sport shoe comprises:

an upper shoe portion defining an interior adapted to receive a foot; and

a foot bed including a base secured to the upper shoe portion, the foot bed defining an upper surface capable of receiving the foot and the base defining a lower surface capable of mounting the lower frame thereon, the foot bed defining a ventilation channel formed within or below the upper surface of the foot bed and at least partially traversing the foot bed from an inlet aperture defined on an exterior of the base to an outlet aperture defined on the exterior of the base, the apertures providing airflow into and out of the foot bed during use, wherein the ventilation channel is in moisture transport communication with the interior of the upper shoe portion, thereby providing a ventilation and moisture transfer from the received foot to the channel and out the outlet aperture, wherein the lower surface of the base defines a projection projecting downwardly from the lower surface, the inlet ventilation aperture being defined within the projection.

Claim 25. (*Original*) The ventilated sport shoe of claim 24, wherein the inlet ventilation aperture is disposed on a forward face of the projection, such that the forward face is oriented towards a toe portion of the base.

Claim 26. (*Original*) The ventilated sport shoe of claim 25, wherein the inlet ventilation aperture is positioned normal to the freestream airflow through the ventilation channel, thereby drawing airflow through the channel.

Claims 27 - 31. (*Canceled*)